



Model	Rated Load at 1.5" Deflection (lbs)	Spring Rate (lbs/in)	Max. Vertical G Rating	Max. Horiz. G Rating	Spring Color
SRMF-1-352	140	93	125.4	29.3	Yellow
SRMF-1-354	250	166	70.2	16.4	Purple
SRMF-1-354-142	385	256	45.6	10.6	Purple/Blue
SRMF-1-356	630	420	27.9	6.5	Black
SRMF-1-356-142	765	510	22.9	5.4	Black/Blue
SRMF-1-356-175	855	570	20.5	4.8	Black/Brown
SRMF-1-356-176	930	620	18.9	4.4	Black/Black
SRMF-1-356-144	1,030	687	17.0	4.0	Black/Brown
SRMF-1-356-146	1,480	988	11.9	2.8	Black/Yellow
SRMF-1-356-148	2,130	1,420	8.2	1.9	Black/Green

Model	Rated Load at 2" Deflection (lbs)	Spring Rate (lbs/in)	Max. Vertical G Rating	Max. Horiz. G Rating	Spring Color
SRMF-1-350	80	40	219.4	51.2	Red
SRMF-1-350-140	160	80	109.7	25.6	Red/Black
SRMF-1-403	348	174	50.4	11.8	Black
SRMF-1-404	453	226.5	38.7	9.0	Blue
SRMF-1-405	590	295	29.7	6.9	Red
SRMF-1-406	676	338	26.0	6.1	Orange
SRMF-1-407	787	393.5	22.3	5.2	Green
SRMF-1-408	918	459	19.1	4.5	White
SRMF-1-409	1,000	500	17.5	4.1	Brown
SRMF-1-410	1,250	625	14.0	3.3	White
SRMF-1-407-150	1,437	718.5	12.2	2.8	Green/Grey
SRMF-1-409-150	1,650	825	10.6	2.5	Brown/Grey
SRMF-1-410-150	1,900	950	9.2	2.2	White/Grey

Notes:

- Standard finish: Housing - Zinc Bright Plating; Spring - Zinc Bright Plating (Color: see table); Hardware - Zinc-electroplate.
- All springs at rated load have 50% additional travel to solid load.
- Safety factor - Springs will accommodate 50% extra load from rated load to solid load.

Isolator Selections			
Pos 1		Pos 2	
Pos 3		Pos 4	
Pos 5		Pos 6	
Pos 7		Pos 8	
Pos 9		Pos 10	

VibraSystems Inc

www.vibrasystems.com
email: info@vibrasystems.com

INSTALLATION INSTRUCTIONS

SCALE: None	MODEL: SRMF-1-350	SHEET 1 OF 2	REV: A
-------------	-------------------	--------------	--------

